



# PRODUCT INFORMATION

## Chakrol 2 T OIL

### DESCRIPTION

**Chakrol 2 T** is a premium quality low smoke two stroke engine oil developed to meet high performance two stroke engines. It is blended from selective base stocks and additives to minimize spark plug fouling, pre-ignition, prevent rusting, minimise deposit formation to provide protection against seizure, scuffing and wear. Chakrol 2T Oil is a green dyed product.

### APPLICATIONS

Chakrol 2 T oils are recommended for engine lubrication of scooters, autorickshaws, motorcycles & mopeds operating on two stroke engines. The recommended dosage of Chakrol 2T Oil is 20ml oil per litre of petrol

### SUPPLY OPTIONS

Despatched and delivered typically in 210 Ltr HDPE Barrels, 50 Ltr, 20 Ltr packs only. Customer specific packs sizes available on request to suit specific requirements.

**SPECIFICATIONS :** Meet/ exceeds JASO FC & API TC specifications.

(Typical data)

<b>Chakrol 2 T Oil</b>	
<b>Properties</b>	<b>Results</b>
Appearance	Clear & Bright Green
Kinematic Viscosity @ 40 °C, cSt	55-60
Flash Point, °C, Min	70
Pour Point, °C, Max	- 12
Sulphated Ash % wt	0.078 – 0.095

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- *Specific requirements can be custom made on request.*
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work & subject to amendment.*

---

For further details please contact: **Sri Rama Lubricants,**

- 153/5/2, Manapet, Kanniakoil, Pondicherry 607402, INDIA. Tel: (+91) 413 2611518.
- Web site: [www.chakrol.com](http://www.chakrol.com), e-mail id: sales@chakrol.com.