



PRODUCT INFORMATION

Chakrol CF/SJ SAE 20W40 Oils

DESCRIPTION

Chakrol CF/SJ Multi Grade oils are high quality diesel engine oils designed for the lubrication of units burning low sulphur distillate fuels. Chakrol CF/SJ Multi Grade Engine Oils are designed with high detergent additive system. These oils have excellent Total Base Number (TBN) retention to ensure protection throughout the oil drain period. It has enhanced protection against corrosion and wear.

Chakrol CF/SJ Multi Grade Oils provides reliable all-year round performance in the application for which they are intended.

APPLICATIONS

Chakrol CF/SJ Multi Grade oils are designed for use in long distance trucking and constant speed on road operations.

SUPPLY OPTIONS

Chakrol CF/SJ Multi Grade Oils are dispatched and delivered in 210 lit. Steel , 50 Lit & 20 lit. HDPE Containers.

SPECIFICATIONS

Chakrol CF/SJ Multi Grade Oils are blended to meet **IS 13656:1993 & U S MIL 2104C & API CF/SJ spec's**. These oils can be blended as per the customer specifications or in different viscosities and international standards as per the requirements of the customers.

Properties	SAE VISCOSITY GRADE	Test Method
	20W40	
Density, Kg/L 15.5 C	0.880	ASTM D 1298
Kinematic Viscosity @ 100°C, cSt	14.0 -16.0	ASTM D 445
Viscosity Index	110 min	ASTM D 2270
Flash Point,COC	220 °C min	ASTM D 92
Pour Point °C,	-21 °C max	ASTM D 97
TBN, mgKOH/gm	10.0 min.	ASTM D2896

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- ***Specific requirements can be custom made on request.***
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact; **Sri Rama Lubricants** ,

- 153/5/2,Manapet,Kanniakoil,Pondicherry 607402 , INDIA. Tel: (+91) 4132611518.
- Web site : www.chakrol.com , e mail id : sales@chakrol.com