



# PRODUCT INFORMATION

## Chakrol Graphite Grease

### DESCRIPTION

**Chakrol** Graphite Grease are designed for high load chassis lubrication. The grease is made of calcium soap thickened grease with colloidal graphite. This grease is recommended for very severe lubrication conditions encountered at very low speed in large open grease drives.

### PROPERTIES

**Chakrol** Graphite grease exhibits excellent water resistance, Lasting qualities in spring shackles and steering connections. It acts as protective layer on exposed parts and thereby aids in preventing rusting & corrosion.

### APPLICATIONS

**Chakrol** Graphite Grease recommended for lubrication of open gear drives of rotary kilns, cement mills, sintering plants and ball mills.

### SUPPLY OPTIONS

**Chakrol** Graphite Grease packed in 180 Kgs. Steel Barrels & 20 Kgs. HDPE plastic containers.

### SPECIFICATIONS :

(Typical Data)

Characteristics	Test Method	Chakrol Graphite Grease
Texture	Visual	Black, Smooth, and Sticky
Consistency @ 25 ° C	ASTM D 217	290 - 310
Drop Point ° C	ASTM D 566	90
Graphite Content %	ASTM D 128	9

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- *Specific requirements can be custom made on request.*
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact; **M/s Sri Chakra Lubes Pvt.Ltd**

- 153/5,Manapet,Kannia Koil, Pondicherry 607402, INDIA. Tel: (+91 )413 2611518
- web site : [www.chakrol.com](http://www.chakrol.com) , e-mail id : sales@chakrol.com