



PRODUCT INFORMATION

Chakrol Calciplex Grease

Description

Chakrol Calciplex Greases are premium quality calcium complex greases intended for the lubrication of roll mills bearings with heavy load operations under wet conditions & high temperatures. It has high drop point of more than 250⁰C, good thermal stability, high degree of resistance to water wash out, oxidation inhibition and protection against rust & corrosion.

Properties

Chakrol Calciplex greases exhibit optimum shear stability, low oil separation and good rust, excellent water washout and oxidation inhibiting properties. These greases have smooth texture and dropping point above 250⁰C to ensure adequate performance in a wide temperature range of -10⁰C to +150⁰C .

Applications:

Chakrol Calciplex Greases are recommended for all classes of service in automotive and industrial lubrication. The maximum operating temperature of these greases is 220⁰C max.

Supply Options:

Chakrol Calciplex Greases are available in 180 Kgs. M.S Drums & 20 Kgs. HDPE Pails.

Specifications :

(Typical Data)

Characteristics	Test Method	Chakrol Calciplex
Texture	Visual	Smooth, Brown Homogeneous
Consistency @ 25 ⁰ C	ASTM D 217	265 – 295
Drop Point ⁰ C (min)	ASTM D 2265	250
Weld Load, Kgs (min)	ASTM D 2596	300

- *NLGI 3 Grade is also made available on specific customer requests.*
- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected during manufacture .*
- ***Specific requirements can be custom made on request.***
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact; **Sri Chakra Lubes Pvt.Ltd**

- 153/5, Manapet,Kanniakoil,Pondicherry 607402 , INDIA . Tel: (+91) 413 2611518.
- web site: www.chakrol.com , e-mail:sales@chakrol.com