



PRODUCT INFORMATION

Chakrol Mould Releasing Lubricant

DESCRIPTION

Chakrol Mould Releasing Lubricant is a premium quality Mould releasing Lubricant designed for continuous casting with wet ability additive system. Chakrol Mould Releasing Lubricant provides reliable all-year round performance in the application for which they are intended.

APPLICATIONS

Chakrol Mould Releasing Lubricant oil recommended inside the mould tube through a feeding device for the purpose of preventing the cast billet from adhering to the inside of mould tube by burning.

SUPPLY OPTIONS

Chakrol Oils Mould Releasing Lubricant is dispatched and delivered in 210 Ltr Mild Steel Barrels or HDPE barrels.

SPECIFICATIONS

(Typical)

Properties	Chakrol Mould Releasing Lubricant	Test Method
Density, Kg/L 15.0 C	0.867 – 0.880	ASTM D 1298
Kinematic Viscosity @ 40°C, cSt	35-50	ASTM D 445
Viscosity Index	100 min	ASTM D 2270
Flash Point, COC	280 °C min	ASTM D 92
Pour Point °C,	-6 °C min	ASTM D 97
Saponification Value, mg KOH/gm	80 max.	ASTM D 94

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- *Specific requirements can be custom made on request.*
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work & subject to amendment.*

For further details please contact; **M/s Sri Rama Lubricants.,**

- 153/5/2, Manapet, Kanniakoil, Pondicherry 607402, INDIA. Tel: (+91) 413 2611518.
- Web site: www.chakrol.com, e-mail id: sales@chakrol.com.