



PRODUCT INFORMATION

Chakrol SF/CD SAE 30,40 & 50 Oils

DESCRIPTION

Chakrol SF/CD Mono Grade Engine Oils are premium quality Petrol & Diesel Engine oils. These monograde lubricants exhibiting very high level of detergency/dispersancy. Chakrol SF/CD Mono Grade Oils are manufactured with high Viscosity Index Base Oils and superior quality additives possessing anti wear, anti corrosion, anti rust and anti oxidant properties.

APPLICATIONS:

Chakrol SF/CD Mono Grade Engine oils are recommended for the protection of new engines, both diesel and petrol fueled. These are used for protecting interior engine components against rust and corrosion during production, storage and transportation stages.

SUPPLY OPTIONS:

Despatched and delivered typically in 210 Ltr HDPE Barrels, 50 Ltr, 20 Ltr & 7.5 Ltr packs. Customer specific packs sizes are available on request to suit specific requirements.

SPECIFICATIONS: Meets/Exceeds API SF/CD & MIL-L-2104B specification.
(Typical Data)

PHYSICAL CHARACTERISTICS	TYPICAL VALUES		
	SAE 30	SAE 40	SAE 50
Appearance	B & C	B & C	B & C
Kinematic Viscosity @ 100 °C	11.5	14.5	18.5
Viscosity Index, Min	95	90	90
Flash Point, °C, Min	210	220	230
Pour Point, °C, Max	- 6	- 6	- 6
TBN, mg KOH/gm	5.1	5.1	5.1

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- **Specific requirements can be custom made on request.**
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact; **Sri Rama Lubricants**,

- 153/5/2, Manapet, Kanniakoil, Pondicherry 607402, INDIA .Tel: (+91)413 2611518.
- Web site: www.chakrol.com, e mail: sales@chakrol.com