



PRODUCT INFORMATION

Chakrol SF/CD 20W40 & 20W50 Oils

DESCRIPTION

Chakrol SF/CD Multi grade engine oils are premium quality Petrol and Diesel Engine oils. These are multi grade lubricants exhibiting very high level of detergency/dispersancy. Chakrol SF/CD Multi grade Engine Oils are manufactured with High Viscosity Index Base Oils and superior quality additives possessing anti wear, anti corrosion, anti rust & anti oxidant properties. They meet/exceed API SF/CD specification and MIL-L-2104 B specification.

APPLICATIONS

Chakrol SF/CD Multi grade engine oils are recommended for the protection of new engines, both diesel and petrol fueled. These are used for protecting interior engine components against rust and corrosion during production, storage and transportation stages.

SUPPLY OPTIONS

Despatched and delivered typically in 210 litres HDPE Barrels, 20 Ltr, 10Ltr, 7.5 Ltr & 5 Ltr HDPE Containers.

SPECIFICATIONS

Chakrol Oils are available in the following grades:

PHYSICAL CHARACTERISTICS	TYPICAL VALUES	
	20W40	20W50
Chakrol SF/CD SAE :	20W40	20W50
Appearance	Reddish	Reddish
Kinematic Viscosity @ 100 °C, cSt	14-16	14-16
Viscosity Index, Min	110	120
Flash Point, °C, Min	210	220
Pour Point, °C, Max	- 21	- 21
TBN, mg KOH/gm	5.1	5.1

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- *Specific requirements can be custom made on request.*
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact; **Sri Rama Lubricants**,

- 153/5/2, Manapet, Kannia Koil, Pondicherry – 607402, INDIA .Tel: (+91) 413 2611518
- web site : www.chakrol.com , e mail id: sales@chakrol.com