



PRODUCT INFORMATION

Chakrol CI4 15W-40 Oils

Description

Chakrol CI 4 15W-40 high quality diesel engine oils designed for the lubrication of units burning low sulphur distillate fuels & are designed with high detergent additive system. These oils have excellent Total Base Number (TBN) retention to ensure protection throughout the oil drain period. It has enhanced protection against corrosion and wear.

Chakrol CI4 15W-40 Oils provide reliable all-year round performance in the application for which they are intended.

Applications

Chakrol CI4 15W-40 oils are designed for use in long distance trucking and constant speed on road operations.

Supply Options:

Despatched and delivered typically in 210 Ltr HDPE Barrels, 50 Ltr, 20 Ltr & 7.5 Ltr packs. Customer specific packs sizes are available on request to suit specific requirements.

Specifications: Meets API CI4, ACEA E5/E7, Volvo VDS-3, MB 228.3 & EDL- 6 of IS: 13656-1993.

Property	SAE VISCOSITY GRADE	Test Method
	15W40	
Density, Kg/L 15.5 C	0.870	ASTM D 1298
Kinematic Viscosity @ 100°C, cSt	14.0 -16.0	ASTM D 445
Viscosity Index	130 min	ASTM D 2270
Flash Point, COC	220 °C min	ASTM D 92
Pour Point °C,	-27 °C max	ASTM D 97
TBN, mgKOH/gm	9.0 min.	ASTM D2896

- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected in manufacture.*
- **Specific requirements can be custom made on request.**
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact:

M/s Sri Rama Lubricants.,

153/5/2, Manapet, Kanniakoil, Pondicherry 607402, INDIA .Tel: (+91)413 2611518.

Web site : www.chakrol.com , e-mail id: sales@chakrol.com