



PRODUCT INFORMATION

Chakrol Alucom Greases

Description

Chakrol Alucom Greases are premium quality aluminum complex greases designed for low speed heavy load operations with high operating temperatures. It has high drop point of more than 250⁰ C, good thermal stability, offers very high degree of resistance to water wash out and protection against rust & corrosion.

Properties

Chakrol Alucom greases are very versatile products with excellent water resistant properties, possessing good anti-shock, anti-scoring, anti-welding & anti-wear properties. These greases have smooth texture and dropping point above 250⁰ C to ensure longer service life and protection against rust and corrosion.

Applications

Chakrol Alucom Greases are recommended for all classes of service in automotive and industrial bearing lubrication viz. in Steel Mills, Paper Wet Section Rolls, Crusher Bearings, De-Watering Press Bearings, Bucket Wheel Excavators.

Note: This grease if being used for the first time, check compatibility with the grease applied previously and if necessary purge the bearings prior to application. Take care not to over pack the bearing with lubricant. Apply the quantity of grease as recommended by the bearing manufacturer.

Supply options

Chakrol Alucom Greases are available in 180 Kgs. M.S Drums & 20 Kgs. HDPE Pails.

Specifications :

(Typical Data)

Characteristics	Test Method	Chakrol Alucom 2
Texture	Visual	Smooth, Homogeneous
Consistency @ 25 ⁰ C	ASTM D 217	265 – 295
Drop Point ⁰ C	ASTM D 2265	>250
Weld Load, Kgs (min)	ASTM D 2596	315

- *NLGI 3 is also made available on specific customer requests.*
- *The above data is indicative of recent averages values only. Minor variations that do not affect product performance or quality may be expected during manufacture .*
- ***Specific requirements can be custom made on request.***
- *The above information is supplied to the best of our knowledge and belief, on the basis of the current state-of-art and our own development work. Subject to amendment.*

For further details please contact; **Sri Chakra Lubes Pvt.Ltd**

- 153/5,Manapet,Kanniakoil,Pondicherry 607402 , INDIA . Tel: (+91) 413 2611518.
- web site: www.chakrol.com , e-mail:sales@chakrol.com